

# EXRATE<sup>®</sup>

Getting you in pole position

## PRODUCT CATALOGUE



EXRATE | Getting you in pole position

EXRATE produces modern, high-performance lubricants with up-to-date specifications and formulated by using only the world's finest base oils and advanced additives. Our factory has the ISO-9001:2008 and ISO-14001:2004 certificate and never loses sight of security, health and environment. All outgoing lubricants are monitored under supervision of the QHSE manager and the manager Operations whereas the laboratory is responsible for quality clearance of initially blocked production batches.

At EXRATE, reliability, quality and partnership are of the utmost importance. As an international business, specialized in lubricants for the after-market, we value our customers. We believe in the power of reliable quality and we invest in business relationships based on mutual respect. Excellent customer service and sharing our knowledge about lubricants, innovations and the environment is meaningful and helps you to meet the ever-changing demands in the market.

EXRATE will get you in pole position!

**EXRATE**<sup>®</sup>  
Getting you in pole position



# Content

<b>Motor Oils Automotive</b>	<b>4</b>
Synthetic multigrades passenger car	4
Mineral multigrades passenger car	6
Synthetic multigrades heavy duty	7
Mineral multigrades heavy duty	9
Mineral singlegrades	10
<b>Gear Oils</b>	<b>12</b>
Manual transmission oils	12
Automatic transmission oils	14
<b>Agriculture products</b>	<b>16</b>
Agriculture STOU oils	16
Agriculture UTTO oils	17
<b>Two-wheeler products</b>	<b>18</b>
Two-stroke motor oils	18
<b>Hydraulic oils</b>	<b>20</b>
Hydraulic oils	20



Disclaimer:

No rights may be derived from the content of this brochure. Changes in product assortment, technical information and typing errors are reserved.

## Motor oils automotive

Synthetic multigrades passenger car



### Alpha 0W-20

Alpha 0W-20 is an extremely low-viscosity, fuel-saving motor oil, suitable for modern petrol and diesel engines in cars and vans. Its special composition means that this product is also ideally suited for use at very low outdoor temperatures, such as those that may occur under Arctic conditions.

**specifications**

ACEA A1/B1-12, Volvo VCC RBS0-2AE

**part.nr. packaging**

58128 1 x 18 lt can  
58129 1 x 25 lt can  
58130 1 x 60 lt drum  
53265 1 x 208 lt drum

**ean**

8710128581283  
8710128581290  
8710128581306  
8710128532650



### Alpha 0W-40

Alpha 0W-40 is a universal, fully-synthetic motor oil, suitable for all (turbocharged) petrol and (turbocharged) diesel engines (both directly and indirectly injected). Alpha 0W-40 can be used in cars and vans that require the specifications set out in the product sheet.

**specifications**

ACEA A3/B4-12, API SN/CF, Meets the requirements of, MB 229.3/226.5, VW 502.00/505.00, BMW Longlife-01, Renault RNO700/RNO710, Porsche A40

**part.nr. packaging**

53135 12 x 1 lt bottle  
53272 4 x 5 lt can  
53230 1 x 18 lt can  
53232 1 x 25 lt can  
53233 1 x 60 lt drum  
53231 1 x 200 lt drum

**ean**

8710128531356  
8710128532728  
8710128532308  
8710128532322  
8710128532339  
8710128532315



### Alpha LL III 5W-30

Alpha LL III 5W-30 is a universal synthetic Low SAPS motor oil. This Long Life motor oil has been specially developed for cars and vans from the VAG group, Mercedes, BMW, and others. Alpha LL III 5W-30 is suitable for petrol and diesel engines, both with and without Unit Injector technology. Also suitable for extended oil change intervals and cars with a particulate filter.

**specifications**

ACEA C3-12, API SN, Meets the requirements of, VW 504.00/507.00, MB 229.51, BMW Longlife-04, Porsche C30

**part.nr. packaging**

53015 12 x 1 lt bottle  
53014 4 x 5 lt can  
53246 1 x 18 lt can  
53247 1 x 25 lt can  
53012 1 x 60 lt drum  
53250 1 x 200 lt drum  
53136 1 x 208 lt drum

**ean**

8710128530151  
8710128530144  
8710128532469  
8710128532476  
8710128530120  
8710128532506  
8710128531363



### Alpha Special 5W-30

Alpha Special 5W-30 is a fuel-saving synthetic motor oil. Suitable for petrol and diesel engines in cars and vans. If the manufacturer so requires, extended oil change intervals are possible. The product complies with the Mid SAPS requirements by Mercedes-Benz (MB 229.51) and BMW (BMW LL-04). Highly suitable for use in the latest BMW and Mercedes-Benz models equipped with a particulate filter and for all vehicles that require ACEA C3 motor oil.

**specifications**

ACEA C3-12, API SN, Meets the requirements of, MB 229.51/229.52, VW 502.00/505.00/505.01, Dexos 2, BMW Longlife-04

**part.nr. packaging**

53011 12 x 1 lt bottle  
53010 4 x 5 lt can  
53237 1 x 18 lt can  
53239 1 x 25 lt can  
53008 1 x 60 lt drum  
53238 1 x 200 lt drum  
53007 1 x 208 lt drum

**ean**

8710128530113  
8710128530106  
8710128532377  
8710128532391  
8710128530083  
8710128532384  
8710128530076

## Motor oils automotive

### Synthetic multigrades passenger car



#### Alpha Special 5W-40

Alpha Special 5W-40 is a premium synthetic motor oil for cars and vans. The special Mid SAPS formula means that this product is suitable for the latest generation of petrol and diesel engines with and without a particulate filter. Consult the product advisory database for the correct application.

##### specifications

ACEA C3-12, API SN/CF, Meets the requirements of, VW 502.00/505.00/505.01, MB 229.51/229.31/226.5, BMW Longlife-04, Ford M2C917-A, Porsche A40, Renault RN0700/RN0710, Dexos 2, Fiat 9.55535-S2

##### part.nr. packaging

53022 12 x 1 lt bottle  
53021 4 x 5 lt can  
53224 1 x 18 lt can  
53226 1 x 25 lt can  
53020 1 x 60 lt drum  
53225 1 x 200 lt drum  
53019 1 x 208 lt drum

##### ean

8710128530229  
8710128530212  
8710128532247  
8710128532261  
8710128530205  
8710128532254  
8710128530199



#### Alpha 5W-30

Alpha 5W-30 is a fuel-saving, synthetic motor oil for the latest generation of cars with a particulate filter and/or catalytic converter. The product is also highly suitable for the latest generation of Ford cars and vans equipped with modern three-way catalytic converters and particulate filters. It can be used if the Ford specification M2C-913-D is recommended and in cases in which one of the older Ford M2C-913-C, M2C-913-B or M2C-913-A specifications is required.

##### specifications

ACEA A1/B1-12, A5/B5-12, API SL/CF, Ford WSS-M2C913-D, Meets the requirements of, Renault RN0700, Jaguar Land Rover STJR.03.5003

##### part.nr. packaging

53018 12 x 1 lt bottle  
53017 4 x 5 lt can  
53240 1 x 18 lt can  
53242 1 x 25 lt can  
53243 1 x 60 lt drum  
53241 1 x 200 lt drum

##### ean

8710128530182  
8710128530175  
8710128532407  
8710128532421  
8710128532438  
8710128532414



#### Alpha 5W-40

Alpha 5W-40 is a universal, fuel-saving synthetic motor oil. The product is suitable for all petrol and diesel engines, both with and without turbochargers, in cars and vans. Always consult the product advisory database for optimal use.

##### specifications

ACEA A3/B4-12, API SN/CF, Meets the requirements of, VW 502.00/505.00, MB 229.3/226.5, Porsche A40, BMW Longlife-01, GM LL-B-025, Renault RN0700/RN0710, Fiat 9.55535-M2

##### part.nr. packaging

53006 12 x 1 lt bottle  
53005 4 x 4 lt can  
53004 4 x 5 lt can  
53003 1 x 18 lt can  
53229 1 x 25 lt can  
53001 1 x 60 lt drum  
53000 1 x 208 lt drum

##### ean

8710128530069  
8710128530052  
8710128530045  
8710128530038  
8710128532292  
8710128530014  
8710128530007



#### Beta 10W-40

Beta 10W-40 is a universal, fuel-saving motor oil, suitable for all petrol and diesel engines, both with and without turbochargers, in cars and vans. Consult the product specifications in the product sheet for correct usage.

##### specifications

ACEA A3/B3-12, A3/B4-08, API SL/CF, Meets the requirements of, MB 229.1

##### part.nr. packaging

53029 12 x 1 lt bottle  
53028 4 x 4 lt can  
53027 4 x 5 lt can  
53026 1 x 18 lt can  
53025 1 x 25 lt can  
53024 1 x 60 lt drum  
53183 1 x 200 lt drum  
53023 1 x 208 lt drum

##### ean

8710128530298  
8710128530281  
8710128530274  
8710128530267  
8710128530250  
8710128530243  
8710128531837  
8710128530236

## Motor oils automotive

### Mineral multigrades passenger car



#### Gamma 15W-40

Gamma 15W-40 is a universal mineral motor oil for petrol, diesel and LPG engines in cars and vans, whether or not fitted with an exhaust gas turbine or catalytic convertor. Always consult the advisory database for optimal use.

##### specifications

ACEA A3/B4-12, API SL/CF, MB 229.1

part.nr.	packaging	ean
53035	12 x 1 lt bottle	8710128530359
53034	4 x 4 lt can	8710128530342
53033	4 x 5 lt can	8710128530335
53184	1 x 18 lt can	8710128531844
53186	1 x 25 lt can	8710128531868
53031	1 x 60 lt drum	8710128530311
53185	1 x 200 lt drum	8710128531851



#### Gamma 20W-50

Gamma 20W-50 is a universal mineral motor oil for petrol, diesel and LPG engines in cars and vans, whether or not fitted with an exhaust gas turbine or catalytic convertor. Always consult the advisory database for optimal use.

##### specifications

ACEA A3/B4-12, API SL/CF

part.nr.	packaging	ean
53040	12 x 1 lt bottle	8710128530403
53039	4 x 4 lt can	8710128530397
53038	4 x 5 lt can	8710128530380
53167	1 x 18 lt can	8710128531677
53235	1 x 25 lt can	8710128532353
53037	1 x 60 lt drum	8710128530373
53234	1 x 200 lt drum	8710128532346



## Motor oils automotive

### Synthetic multigrades heavy duty



#### Delta HDD LA Supreme 5W-30

Delta HDD LA Supreme 5W-30 is a fuel-saving lubricant oil, specially developed for diesel engines that are used in the most severe operating conditions in all seasons. This product is highly suitable for use in EURO 4 and EURO 5 engines in combination with diesel fuels with a low sulfur content. This motor oil is also suitable for use in so-called EGR engines, with or without particulate filters. This motor oil forms part of the Low SAPS group of lubricants.

##### specifications

ACEA E6-12, E7-12, E9-12, API CJ-4/SN, MB-Approval 228.31/228.51, MAN M 3677/M 3477/M 3271-1, Volvo VDS-4/VDS-3, Mack EO-O Premium Plus/EO-N, Renault VI RLD-3/RLD-2, Meets the requirements of, MTU Type 3.1, Renault VI RXD/RGD, Mack EO-M Plus, Cummins CES 20081, Cat ECF-3, Detroit Diesel 93K218, Deutz DQC IV-10 LA, JASO DH-2, Scania Low Ash

part.nr.	packaging
58145	1 x 18 lt can
58146	1 x 25 lt can
58147	1 x 60 lt drum
58107	1 x 208 lt drum

ean
8710128581450
8710128581467
8710128581474
8710128581078



#### Delta HDD LA Supreme 10W-40

Delta HDD LA Supreme 10W-40 is a fuel-saving lubricant oil, specially developed for diesel engines that are used in the most severe operating conditions in all seasons. This product is highly suitable for use in EURO 4, EURO 5 and EURO 6 engines in combination with diesel fuels with a low sulfur content. This motor oil is also suitable for use in engines with or without particulate filters and catalytic converters. This motor oil is part of the Low SAPS group of lubricants.

##### specifications

ACEA E4-12, E6-12, E7-12, E9-12, API CJ-4, Volvo VDS-4, Renault VI RLD-3, MB-Approval 228.31/228.51, MAN M 3477/M 3575/M 3271-1, MTU Type 3.1/2.1, Mack EO-O Premium Plus, Deutz DQC IV-10 LA, Meets the requirements of, Cat ECF-3, Cummins CES 20081, Detroit Diesel 93K218, JASO DH-2, Scania Low Ash, Renault VI RLD-2, Mack EO-N Premium Plus, Voith Class B/MB 235.28

part.nr.	packaging
58148	1 x 18 lt can
58149	1 x 25 lt can
58150	1 x 60 lt drum
58155	1 x 200 lt drum

ean
8710128581481
8710128581498
8710128581504
8710128581559



#### Delta HDD LA 10W-40

Delta HDD LA 10W-40 is a fuel-saving lubricant oil, specially developed for diesel engines that are used in the most severe operating conditions in all seasons. This product is highly suitable for use in EURO 4 and EURO 5 engines in combination with diesel fuels with a low sulfur content. This motor oil is also suitable for use in so-called EGR engines, with or without particulate filters. This motor oil forms part of the Low SAPS group of lubricants.

##### specifications

ACEA E6-12, E7-12, API CI-4, MB-Approval 228.51, MAN M 3477/M 3271-1, Volvo VDS-3, Mack EO-N, Renault VI RLD-2, Meets the requirements of, DAF Long Drain, Renault VI RXD, MB 226.9, MTU Type 3.1, Deutz DQC III-10 LA, JASO DH-2, Cummins CES 20076/20077

part.nr.	packaging
53046	4 x 5 lt can
53248	1 x 18 lt can
53137	1 x 25 lt can
53044	1 x 60 lt drum
53249	1 x 200 lt drum
53043	1 x 208 lt drum

ean
8710128530465
8710128532483
8710128531370
8710128530441
8710128532490
8710128530434



#### Delta HDD Perfect 5W-30

Delta HDD Perfect 5W-30 is suitable for diesel engines operating under the heaviest operating conditions. Suitable for use in diesel engines with very low exhaust gas emissions, in combination with diesel fuels with a very low sulfur content. Delta HDD Perfect 5W-30 has been developed (taking the manufacturers' instructions into account) to facilitate very long oil change intervals (100,000+ km) while retaining a very long and problem-free service life.

##### specifications

ACEA E4-12, E7-12, API CI-4, MB-Approval 228.5, MAN M 3377/M 3277, Volvo VDS-3, Mack EO-N, Renault VI RLD-2, DAF HP1/HP2, Meets the requirements of, Scania LDF, Cat ECF-2, Cummins 20076/20078, Deutz DQC IV-10, Mack EO-M Plus, MTU Type 3, Renault VI RXD, Global DHD-1, JASO DH-1

part.nr.	packaging
58122	1 x 18 lt can
58123	1 x 25 lt can
58124	1 x 60 lt drum
58108	1 x 208 lt drum

ean
8710128581221
8710128581238
8710128581245
8710128581085

## Motor oils automotive

Synthetic multigrades heavy duty



### Delta HDD Perfect 10W-40

Delta HDD Perfect 10W-40 is suitable for modern diesel engines that are required to perform in the most severe operating conditions. Highly suitable for use in diesel engines with low exhaust gas emissions (including EURO 3, 4 and 5), in combination with diesel fuels with a low sulfur content. Delta HDD Perfect 10W-40 has been developed, in keeping with the manufacturers' instructions, to allow very long oil change intervals (100,000+ km) while retaining a very long and problem-free service life.

**specifications**

ACEA E4-12, E7-12, API CI-4, MB-Approval 228.5, MAN M 3377/M 3277, Volvo VDS-3, Renault VI RLD-2, Mack EO-N, Meets the requirements of, Renault VI RXD, MTU Type 3, Deutz IV-10, Mack EO-M Plus, Cummins CES 20078, Global DHD-1, Detroit Diesel 93K215

**part.nr. packaging**

53051 4 x 5 lt can  
53244 1 x 18 lt can  
53049 1 x 25 lt can  
53048 1 x 60 lt drum  
53245 1 x 200 lt drum  
53047 1 x 208 lt drum

**ean**

8710128530519  
8710128532445  
8710128530496  
8710128530489  
8710128532452  
8710128530472



### Delta HDD 10W-40

Delta HDD 10W-40 is a motor oil that is suitable for petrol and diesel engines both with and without turbochargers that are used in the most severe operating conditions in all seasons. This product has a high 'Total Base Number' and is therefore also suitable for use with diesel fuels with a relatively high sulfur content.

This motor oil has been specially developed in order to allow long oil change intervals (45,000 km) and to prevent 'Bore Polishing' (cylinder wall wear).

**specifications**

ACEA A3/B4-12, E7-12, API CI-4/SL, Meets the requirements of, MB 228.3/229.1, MAN M 3275, Volvo VDS-3, Renault VI RLD/RLD-2, MTU Type 2, Cummins CES 20076/20077/20078, Mack EO-N/EO-M Plus, Global DHD-1, Cat ECF-1-a/ECF-2, Deutz QOC III-10, Detroit Diesel 93K215, ZF TE-ML 07C

**part.nr. packaging**

53056 4 x 5 lt can  
53055 1 x 18 lt can  
53054 1 x 25 lt can  
53053 1 x 60 lt drum  
53236 1 x 200 lt drum  
53052 1 x 208 lt drum

**ean**

8710128530564  
8710128530557  
8710128530540  
8710128530533  
8710128532360  
8710128530526



## Motor oils automotive

### Mineral multigrades heavy duty



#### Delta HDD 15W-40

Delta HDD 15W-40 is a motor oil suitable for diesel engines both with and without turbochargers, that are used under the most severe operating conditions in all seasons. Delta HDD 15W-40 has a high 'Total Base Number' and is thus also suitable for use with fuels with a relatively high sulfur content. This motor oil has been specially developed to facilitate long oil change intervals (45,000 km) and to prevent 'Bore Polishing' (cylinder wall wear).

##### specifications

ACEA A3/B4-12, E7-12, API CI-4/SL, Meets the requirements of, MB 228.3/229.1, Volvo VDS-3, FVI RLD/RLD-2, Mack EO-N/EO-M Plus, Cummins CES 20076/20077/20078, MAN M 3275, Cat ECF-1-a/ECF-2, Deutz DCQ III-10, MTU Type 2, Detroit Diesel 93K215, Global DHD-1, ZF TE-ML 07C

##### part.nr. packaging

53061 4 x 5 lt can  
53179 1 x 18 lt can  
53059 1 x 25 lt can  
53058 1 x 60 lt drum  
53189 1 x 200 lt drum  
53057 1 x 208 lt drum

##### ean

8710128530618  
8710128531790  
8710128530595  
8710128530588  
8710128531899  
8710128530571



#### Delta HDD 20W-50

Delta HDD 20W-50 engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals and to prevent 'Bore Polishing' (Cylinder Wear) in diesel engines. Also is this product suitable for application in EURO 3 and EURO 4 engines.

##### specifications

ACEA A3/B4, E7, API CI-4/SL, Meets the requirements of, MB 228.3/229.1, Cummins CES 20076/20077/20078, Global DHD-1, Deutz DCQ III-10

##### part.nr. packaging

53222 1 x 18 lt can  
53064 1 x 25 lt can  
53063 1 x 60 lt drum  
53223 1 x 200 lt drum  
53062 1 x 208 lt drum

##### ean

8710128532223  
8710128530649  
8710128530632  
8710128532230  
8710128530625



#### Delta SHPD 15W-40

Delta SHPD 15W-40 is a universal lubricant oil suitable for petrol and diesel engines both with and without turbochargers, under all operating conditions in all seasons.

If extended oil change intervals (up to 30,000 km) are permitted by the engine manufacturers, this oil can also be used.

##### specifications

ACEA A3/B3-98, E2-96, API CH-4/SJ, Meets the requirements of, MB 228.1, MAN 271, Volvo VDS-2, Renault VI RD/RD-2, Mack EO-M Plus, Cat ECF-1-a, Cummins CES 20071/20076, MTU Type 1, ZF TE ML 04C/07C

##### part.nr. packaging

58125 1 x 18 lt can  
58126 1 x 25 lt can  
58127 1 x 60 lt drum  
53270 1 x 200 lt drum

##### ean

8710128581252  
8710128581269  
8710128581276  
8710128532704



#### Delta SHPD 20W-50

Multifleet SHPD 20W-50 is a universal lubricant oil suitable for petrol and diesel engines with and without turbochargers. The product can be used in all seasons, under all operating conditions. Multifleet SHPD 20W-50 can also be used whenever extended oil change intervals (up to 30,000 km) are permitted by the engine manufacturers.

##### specifications

ACEA A3-98, B3-98, E2-96, API CH-4/SJ, Meets the requirements of, MB 228.1, MAN 271

##### part.nr. packaging

58157 4 x 5 lt can  
58142 1 x 18 lt can  
58143 1 x 25 lt can  
58144 1 x 60 lt drum  
53271 1 x 200 lt drum

##### ean

8710128581573  
8710128581429  
8710128581436  
8710128581443  
8710128532711

## Motor oils automotive

### Mineral singlegrades



### Gamma TD SAE 30

Gamma TD SAE 30 is a universal, single-grade motor oil suitable for petrol and diesel engines, both with and without turbochargers, under all operating conditions.

**specifications**

ACEA E2-96, API SG/CF, Meets the requirements of, MB 227.0/228.0, MAN 270

**part.nr. packaging**

53041 1 x 18 lt can  
58151 1 x 25 lt can  
58152 1 x 60 lt drum  
58153 1 x 200 lt drum

**ean**

8710128530410  
8710128581511  
8710128581528  
8710128581535



### Gamma TD SAE 50

Gamma TD SAE 50 is a universal, single-grade motor oil suitable for petrol and diesel engines, both with and without turbochargers, under all operating conditions.

**specifications**

ACEA E2-96, API SG/CF, Meets the requirements of, MB 227.0/228.0, MAN 270

**part.nr. packaging**

53180 1 x 18 lt can  
58154 1 x 25 lt can  
53181 1 x 60 lt drum  
53182 1 x 200 lt drum

**ean**

8710128531806  
8710128581542  
8710128531813  
8710128531820



### Lawn Mower Oil 4T

Lawn Mower Oil 4T lubricating oil suitable for 4T lawn mower engines.

**specifications**

API SF/CC, CCMC G2/D1

**part.nr. packaging**

53175 12 x 1 lt bottle

**ean**

8710128531752



## Gear oils

### Manual transmission oils



#### Omega Synth 75W-90

Omega Synth 75W-90 is a fuel-saving, fully synthetic transmission oil, suitable for the entire drive line with a premium quality (API: GL5+ level). The product has been developed for use in the most heavy-duty transmissions in manual transmissions, transfer boxes and final drives. Always consult the advisory database for optimal use.

**specifications**

API GL-3/GL-4/GL-5/MT-1, Mil-L-2105D/Mil-PRF-2105E, SAE J2360, MB 235.8, MAN 341 Typ Z2/E3, 342 Typ M3, MB-Approval 235.8, MAN 341 Typ Z2/E3, 342 Typ M3, ZF TE-ML 02B/05B/07A/12L/12N/16F/17B/19C/21B, Meets the requirements of, Scania STO 1:0, DAF, Iveco, Eaton Europe, Volvo 97312, Mack GO-J, ArvinMeritor 076-N, Ford M2C200-B/C, ZF TE-ML 08, MAN 3343 Typ S

**part.nr. packaging**

53079 12 x 1 lt bottle  
53080 4 x 5 lt can  
53078 1 x 18 lt can  
53077 1 x 25 lt can  
53076 1 x 60 lt drum  
53227 1 x 200 lt drum

**ean**

8710128530793  
8710128530809  
8710128530786  
8710128530779  
8710128530762  
8710128532278



#### Omega AX-5 TS 75W-90

Omega AX-5 TS 75W-90 is a fuel-saving synthetic transmission oil and has been developed for use in the most heavy-duty hypoid transmissions in rear axles and manual transmissions. It can also be used in all transmissions in which 'Extreme Pressure' oils are recommended.

**specifications**

API GL-5, Mil-L-2105D, Meets the requirements of, ZF TE-ML 07A/17B

**part.nr. packaging**

53086 12 x 1 lt bottle  
53085 4 x 5 lt can  
53084 1 x 18 lt can  
53083 1 x 25 lt can  
53082 1 x 60 lt drum  
53208 1 x 200 lt drum

**ean**

8710128530861  
8710128530854  
8710128530847  
8710128530830  
8710128530823  
8710128532087



#### Omega GB-4 SAE 80W-90

Omega GB-4 SAE 80W-90 is used in hypoid rear axles, gearboxes and in other transmissions in which 'Extreme Pressure' oil is required.

**specifications**

API GL-4, Mil-L-2105, ZF TE-ML 16A/17A/19A

**part.nr. packaging**

53203 1 x 18 lt can  
53095 1 x 25 lt can  
53205 1 x 60 lt drum  
53204 1 x 200 lt drum

**ean**

8710128532032  
8710128530953  
8710128532056  
8710128532049



#### Omega GB-4 80W

Omega GB-4 80W is used in hypoid rear axles, gearboxes and in other transmissions in which 'Extreme Pressure' oil is required.

**specifications**

API GL-4, Mil-L-2105, MAN 341 Typ Z2/E1, Meets the requirements of, MB 235.1

**part.nr. packaging**

58139 1 x 18 lt can  
53251 1 x 25 lt can  
58140 1 x 60 lt drum  
58141 1 x 200 lt drum

**ean**

8710128581399  
8710128532513  
8710128581405  
8710128581412

## Gear oils

### Manual transmission oils



#### Omega GB-4 SAE 90

Omega GB-4 SAE 90 is used in hypoid rear axles, gearboxes and in other transmissions in which 'Extreme Pressure' oil is required.

**specifications**

API GL-4, Mil-L-2105, Meets the requirements of, ZF TE-ML 16A/17A/19A, MB 235.1

**part.nr. packaging**

53149 4 x 5 lt can  
53144 1 x 18 lt can  
53148 1 x 25 lt can  
53207 1 x 60 lt drum  
53206 1 x 200 lt drum

**ean**

8710128531493  
8710128531448  
8710128531486  
8710128532070  
8710128532063



#### Omega AX-5 SAE 80W-90

Omega AX-5 80W-90 is used in the most heavy-duty hypoid transmissions in rear axles, gearboxes, and in all transmissions in which 'Extreme Pressure' oil is required.

**specifications**

API GL-5, Mil-L-2105D, ZF TE-ML 16B/17B/19B/21A, Meets the requirements of, MAN 342 Typ M1, MB 235.0

**part.nr. packaging**

53092 12 x 1 lt bottle  
53091 4 x 5 lt can  
53090 1 x 18 lt can  
53089 1 x 25 lt can  
53088 1 x 60 lt drum  
53209 1 x 200 lt drum

**ean**

8710128530922  
8710128530915  
8710128530908  
8710128530892  
8710128530885  
8710128532094



#### Omega AX-5 SAE 90

Omega AX-5 SAE 90 is used in the most heavy-duty hypoid transmissions in rear axles, gearboxes, and in all transmissions in which 'Extreme Pressure' oil is required.

**specifications**

API GL-5, Mil-L-2105D, MAN 342 Typ M1, Meets the requirements of, ZF TE-ML 07A/16B/17B/19B/21A, MB 235.0

**part.nr. packaging**

53143 4 x 5 lt can  
53210 1 x 18 lt can  
53212 1 x 25 lt can  
53142 1 x 60 lt drum  
53211 1 x 200 lt drum

**ean**

8710128531431  
8710128532100  
8710128532124  
8710128531424  
8710128532117

## Gear oils

Automatic transmission oils



### Omega DX III G

Omega DX III G is suitable for automatic transmissions, power steering systems, torque converters and other applications for which General Motors and other constructors recommend a type Omega DX III G oil. Consult the product specifications in the product sheet for correct usage.

**specifications**

Dexron IIIH, MB-Approval 236.1, MAN 339 Typ Z1/V1, ZF TE-ML 04D/14A, Allison C4, Meets the requirements of, Ford Mercon, Cat TO-2, ZF TE-ML 02F/03D/09/11B/17C, Voith 55.6335, Volvo 97341

**part.nr. packaging**

53106 12 x 1 lt bottle  
53105 4 x 5 lt can  
53216 1 x 18 lt can  
53103 1 x 25 lt can  
53102 1 x 60 lt drum  
53217 1 x 200 lt drum

**ean**

8710128531066  
8710128531059  
8710128532162  
8710128531035  
8710128531028  
8710128532179



### Omega DX II D

Omega DX II-D can be used for automatic gearboxes, power steering systems, torque converters and other applications for which General Motors and other constructors recommend a type Omega DX II-D oil.

**specifications**

GM Dexron IID, MB-Approval 236.7, MAN 339 Typ Z1, Meets the requirements of, ZF TE-ML 09/11A/14A, Allison C4, Ford SQM-2C9010-A, Voith 55.6335 (G607), Cat TO-2, Renk, MAN 339 Typ V1, Ford M2C138-CJ/166-H

**part.nr. packaging**

53101 12 x 1 lt bottle  
53100 4 x 5 lt can  
53099 1 x 18 lt can  
53214 1 x 25 lt can  
53215 1 x 60 lt drum  
53213 1 x 200 lt drum

**ean**

8710128531011  
8710128531004  
8710128530991  
8710128532148  
8710128532155  
8710128532131





## Agriculture products

### Agriculture STOU oils



#### Supertrac 10W-40

Supertrac 10W-40 has been specially developed for everyday operating conditions in agriculture. The universal, multifunctional oil is what is known as an STOU: Super Tractor Oil Universal. It is therefore suitable for use as an all-purpose lubricant for: Petrol engines | Diesel engines and turbo diesels | Transmissions, also for wet brakes | Hydraulic systems

**specifications**

API SF/CG-4/GL-4, Meets the requirements of, ZF TE-ML 06B/07B, MB 227.1

**part.nr. packaging**

53150 1 x 18 lt can  
53125 1 x 25 lt can  
53151 1 x 60 lt drum  
53193 1 x 200 lt drum

**ean**

8710128531509  
8710128531257  
8710128531516  
8710128531936



#### Unitrac 10W-30

Unitrac 10W-30 has been specially developed for everyday operating conditions in agriculture. The universal, multifunctional oil is what is known as an STOU: Super Tractor Oil Universal. It is therefore suitable for use as an all-purpose lubricant for: Petrol engines | Diesel engines and turbo diesels | Transmissions, also for wet brakes | Hydraulic systems

**specifications**

API SF/CG-4/GL-4, Meets the requirements of, Ford M2C159-C, ZF TE-ML 06B/07B, MB 227.1

**part.nr. packaging**

53131 4 x 5 lt can  
53130 1 x 18 lt can  
53129 1 x 25 lt can  
53127 1 x 60 lt drum  
53190 1 x 200 lt drum  
53126 1 x 208 lt drum

**ean**

8710128531318  
8710128531301  
8710128531295  
8710128531271  
8710128531905  
8710128531264



#### Unitrac 15W-30

Unitrac 15W-30 has been specially developed for everyday operating conditions in agriculture. The universal, multifunctional oil is what is known as an STOU: Super Tractor Oil Universal. It is therefore suitable for use as an all-purpose lubricant for: Petrol engines | Diesel engines and turbo diesels | Transmissions, also for wet brakes | Hydraulic systems

**specifications**

API SF/CG-4/GL-4, Meets the requirements of, Ford M2C159-C, ZF TE-ML 06B/07B, MB 227.1

**part.nr. packaging**

53168 1 x 18 lt can  
53133 1 x 25 lt can  
53192 1 x 60 lt drum  
53191 1 x 200 lt drum

**ean**

8710128531684  
8710128531332  
8710128531929  
8710128531912

## Agriculture products

### Agriculture UTTO oils



#### Unitrans 56

Unitrans 56 is a UTTO (Universal Tractor Transmission Oil), developed specially for everyday operating conditions in the agricultural industry. This universal oil has been developed as a lubricant oil for the hydraulic and transmission systems of the most common agricultural and earth-moving machines.

**specifications**

API GL-4, Meets the requirements of, Ford M2C134-D, CNH MAT 3525, John Deere J20C, Massey Ferguson M1141/M1143, Cat TO-2, IH Plus (suitable for use), Case MS1206/MS1207 (suitable for use), Case MAT 3505/MS 1209 (suitable for use)

**part.nr. packaging**

58133 1 x 18 lt can  
58134 1 x 25 lt can  
58135 1 x 60 lt drum  
53264 1 x 200 lt drum

**ean**

8710128581337  
8710128581344  
8710128581351  
8710128532643



#### Unitrans 67

Unitrans 67 is a UTTO (Universal Tractor Transmission Oil), developed specially for everyday operating conditions in the agricultural industry. This universal oil has been developed as a lubricant oil for the hydraulic and transmission systems of the most common agricultural and earth-moving machines.

**specifications**

API GL-4, Meets the requirements of, Ford M2C134-D, CNH MAT 3525, John Deere J20C, Massey Ferguson M1135/M1141/M1143, Volvo WB 101, Allison C4, Cat TO-2, ZF TE-ML 03E/05F/06K, NH 410B, Case MS1206/MS1207/MS1210

**part.nr. packaging**

58136 1 x 18 lt can  
58137 1 x 25 lt can  
58138 1 x 60 lt drum  
53273 1 x 200 lt drum

**ean**

8710128581368  
8710128581375  
8710128581382  
8710128532735

## Two-wheeler products

### Two-stroke motor oils



### Beta 2T

Beta 2T has been developed specifically for high speed and heavy-duty (air or water-cooled) 2-stroke scooter engines. Furthermore, the product can be successfully used in other 2-stroke engines such as motorcycles, chainsaws and generators. For the best result, mix 1 part Beta 2T to 50 parts unleaded petrol or use the mixing ratio recommended by the manufacturer. Beta 2T is a self-mixing, semi-synthetic 2-stroke motor oil that is also suitable for automatic lubrication systems.

#### specifications

API TC, JASO FD, ISO-L-EGD, Global GD, Husqvarna 272, 2-Stroke DFI

#### part.nr. packaging

53134 12 x 1 lt bottle  
53218 1 x 18 lt can  
53220 1 x 25 lt can  
53221 1 x 60 lt drum  
53219 1 x 200 lt drum

#### ean

8710128531349  
8710128532186  
8710128532209  
8710128532216  
8710128532193





## Hydraulic oils

Hydraulic oils



### Lube HVLP 32

Lube HVLP 32 is ideally suited to all heavy-duty hydraulic systems in earth-moving machinery and in fixed installations that are required to work under high pressures and within a wide temperature range.

**specifications**

DIN 51524-3 HVLP, AFNOR NF E 48-603 HV, ISO 11158 HV, ASTM D 6158 HV, Denison HF-0/HF-1/HF-2, Cincinnati Machine P-68, Eaton Brochure 694 for 35VQ25A, GM LS-2

part.nr.	packaging
58114	1 x 18 lt can
58115	1 x 25 lt can
58116	1 x 60 lt drum
58117	1 x 200 lt drum

ean
8710128581146
8710128581153
8710128581160
8710128581177



### Lube HVLP 46

Lube HVLP 46 is ideally suited to all heavy-duty hydraulic systems in earth-moving machinery and in fixed installations that are required to operate under high pressures and within a wide temperature range.

**specifications**

DIN 51524-3 HVLP, AFNOR NF E 48-603 HV, ISO 11158 HV, ASTM D 6158 HV, Denison HF-0/HF-1/HF-2, Cincinnati Machine P-70, Eaton Brochure 694 for 35VQ25A, GM LS-2

part.nr.	packaging
53124	1 x 18 lt can
53201	1 x 25 lt can
53202	1 x 60 lt drum
53200	1 x 200 lt drum
53121	1 x 208 lt drum

ean
8710128531240
8710128532018
8710128532025
8710128532001
8710128531219



### Lube HVLP 68

Lube HVLP 68 is ideally suited to all heavy-duty hydraulic systems in earth-moving machinery and in fixed installations that are required to operate under high pressures and within a wide temperature range.

**specifications**

DIN 51524-3 HVLP, AFNOR NF E 48-603 HV, ISO 11158 HV, ASTM D 6158 HV, Denison HF-0/HF-1/HF-2, Cincinnati Machine P-69, Eaton Brochure 694 for 35VQ25A, GM LS-2

part.nr.	packaging
58118	1 x 18 lt can
58119	1 x 25 lt can
58120	1 x 60 lt drum
58121	1 x 200 lt drum

ean
8710128581184
8710128581191
8710128581207
8710128581214



### Lube HLP 32

Lube HLP 32 is suitable both for heavy-duty hydraulic installations and for gearbox transmissions and bearings subject to light loads. Furthermore, Lube HLP 32 is also highly suitable for use as circulation lubrication (with the exception of turbines), for vacuum pumps and general machine lubrication.

**specifications**

DIN 51524-2 HLP, AFNOR NF E 48-603 HM, ISO 11158 HM, ASTM D 6158 HM, Denison HF-0/HF-1/HF-2, Cincinnati Machine P-68, Eaton Brochure 694 for 35VQ25A, GM LS-2

part.nr.	packaging
53111	4 x 5 lt can
53110	1 x 18 lt can
53195	1 x 25 lt can
53108	1 x 60 lt drum
53194	1 x 200 lt drum
53107	1 x 208 lt drum

ean
8710128531110
8710128531103
8710128531950
8710128531080
8710128531943
8710128531073



## Hydraulic oils

### Hydraulic oils



#### Lube HLP 46

Lube HLP 46 is suitable both for heavy-duty hydraulic installations and for gear transmissions and bearings subject to light loads. Furthermore, Lube HLP 46 is also highly suitable for use as circulation lubrication (with the exception of turbines), for vacuum pumps and general mechanical lubrication.

**specifications**

DIN 51524-2 HLP, AFNOR NF E 48-603 HM, ISO 11158 HM, ASTM D 6158 HM, Denison HF-0/HF-1/HF-2, Cincinnati Machine P-70, Eaton Brochure 694 for 35VQ25A, GM LS-2

**part.nr. packaging**

53116 4 x 5 lt can  
53115 1 x 18 lt can  
53114 1 x 25 lt can  
53113 1 x 60 lt drum  
53196 1 x 200 lt drum  
53112 1 x 208 lt drum

**ean**

8710128531165  
8710128531158  
8710128531141  
8710128531134  
8710128531967  
8710128531127



#### Lube HLP 68

Lube HLP 68 is suitable both for heavy-duty hydraulic installations and for gear transmissions and bearings subject to a light load. Furthermore, Lube HLP 68 is also highly suitable for use as circulation lubrication (with the exception of turbines), for vacuum pumps and general mechanical lubrication.

**specifications**

DIN 51524-2 HLP, AFNOR NF E 48-603 HM, ISO 11158 HM, ASTM D 6158 HM, Denison HF-0/HF-1/HF-2, Cincinnati Machine P-69, Eaton Brochure 694 for 35VQ25A, GM LS-2

**part.nr. packaging**

53120 1 x 18 lt can  
53198 1 x 25 lt can  
53199 1 x 60 lt drum  
53197 1 x 200 lt drum  
53117 1 x 208 lt drum

**ean**

8710128531202  
8710128531981  
8710128531998  
8710128531974  
8710128531172

[www.exrate.eu](http://www.exrate.eu)